Contents

| Ał | Abstract | | | | | | | |
|-----------------|---|---------|--|----|--|--|--|--|
| Acknowledgments | | | | | | | | |
| 1 | Intro | oductio | n | 1 | | | | |
| | 1.1 | Proble | m Statement | 1 | | | | |
| | 1.2 | Contri | butions | 3 | | | | |
| | 1.3 | Thesis | 3 Outline | 6 | | | | |
| 2 | Dyn | amics | and Active Vibration Control of the Lightweight Stress-Ribbon Footbridge | 7 | | | | |
| | 2.1 | Static | and Dynamic Characteristics of a Stress-Ribbon Bridge | 7 | | | | |
| | 2.2 | Dynar | nics of the CFRP Stress-Ribbon Footbridge | 12 | | | | |
| | | 2.2.1 | Structural Characteristics | 13 | | | | |
| | | 2.2.2 | Finite-Element Modelling and Modal Characteristics | 14 | | | | |
| | | 2.2.3 | Pedestrian-Induced Vibration of the Stress-Ribbon Bridge | 23 | | | | |
| | | 2.2.4 | Time-Varying Modal Characteristics of the Footbridge | 26 | | | | |
| | 2.3 | Active | Vibration Control of the Stress-Ribbon Bridge | 28 | | | | |
| | | 2.3.1 | Experimental Setups | 30 | | | | |
| | | 2.3.2 | Vibration Control with State-Space Models | 35 | | | | |
| | | 2.3.3 | State-Space Modelling with White-Box Models | 38 | | | | |
| 3 | Ехр | erimen | tal System Identification for Active Vibration Control | 45 | | | | |
| | 3.1 | Introd | | 45 | | | | |
| | 3.2 | Black- | Box System Identification Based on SIM | 47 | | | | |
| | | 3.2.1 | Subspace Identification Algorithm | 47 | | | | |
| | | 3.2.2 | Modal Transformation and Model Validation | 49 | | | | |
| | 3.3 Black-Box Identification Based on SIM | | Box Identification Based on SIM | 52 | | | | |
| | | 3.3.1 | Design of Stochastic Excitation Signals | 53 | | | | |
| | | 3.3.2 | Experimental Subspace Identification | 54 | | | | |
| | | 3.3.3 | Model Validation | 60 | | | | |
| | 3.4 | Grey-I | Box Identification Based on PEM | 63 | | | | |
| | | 3.4.1 | Predefined Model Structure | 63 | | | | |
| | | 3.4.2 | Parameter Estimation and Model Verification | 67 | | | | |

| | | 3.4.3 Comparative Analysis of Black-Box and Grey-Box System Identification | 73 | | |
|--------------|------|---|-----|--|--|
| | 3.5 | Summary | 75 | | |
| 4 | Mult | ti-Modal State Estimation Based on Inertial Sensors | 77 | | |
| | 4.1 | | 77 | | |
| | 4.2 | Drift-free Estimation of Velocity/Displacement from an Accelerometer | 80 | | |
| | | 4.2.1 Band-Limited Multiple FLC | 80 | | |
| | | 4.2.2 Estimation of BMFLC with KF | 81 | | |
| | | 4.2.3 Calculation of Displacements and Velocities | 82 | | |
| | 4.3 | State Estimation of Vertical and Torsional Modes in Setup C | 84 | | |
| | | 4.3.1 Sensor Information Fusion from Multiple Sensors | 84 | | |
| | | 4.3.2 Weighted Fusion KF with Inertial Sensors | 86 | | |
| | 4.4 | Experimental Verification of Multi-Modal State Estimation | 86 | | |
| | | 4.4.1 Experimental Verification of Nodal State Estimation with Accelerometers | 87 | | |
| | | 4.4.2 Experimental Verification of Rotation Angles with Gyroscopes | 89 | | |
| | | 4.4.3 Real-Time Estimation of Vertical and Torsional Modes | 90 | | |
| | 4.5 | Conclusions | 93 | | |
| 5 | Mult | ti-Modal Active Vibration Control for the Stress-Ribbon Bridge | 95 | | |
| | 5.1 | Challenges in AVC of the Bridge | 96 | | |
| | 5.2 | Modal Control Law for AVC of the Bridge | 97 | | |
| | | 5.2.1 Modal Control Law of Multiple Modes of Interest | 98 | | |
| | | 5.2.2 Optimal Sensor Position for Modal State Estimation | 101 | | |
| | | 5.2.3 Multi-Modal Control of the Stress-Ribbon bridge | 110 | | |
| | | 5.2.4 Time-Delayed Modal Velocity Feedback Control | 112 | | |
| | 5.3 | Stability Analysis due to Changing Modal Characteristic | 120 | | |
| | 5.4 | Overview of the Designed Multi-Modal AVC | 122 | | |
| 6 | Sim | ulation and Experimental Verification | 127 | | |
| | 6.1 | Simulation of Multi-Modal Active Vibration Control | 127 | | |
| | | 6.1.1 Simulation of AVC with 2D Models in Setup B2 | 128 | | |
| | | 6.1.2 Simulation of AVC with 3D Models in Setup C | 129 | | |
| | 6.2 | Experimental Verification of the Designed Controller | 132 | | |
| | | 6.2.1 AVC of Vertical Modes in Setup B2 | 133 | | |
| | | 6.2.2 AVC of the Stress-Ribbon Bridge in Setup C | 135 | | |
| | | 6.2.3 AVC of Superposed Resonance Vibration in Multiple Modes | 139 | | |
| | 6.3 | Active Vibration Control of Pedestrian Induced Vibration | 143 | | |
| 7 | Con | clusions and Recommendations | 151 | | |
| | 7.1 | Conclusions | 151 | | |
| | 7.2 | Recommendations for Further Research | 153 | | |
| Bibliography | | | | | |

viii

| Aŗ | Appendices | | |
|----|---|-----|--|
| A | Time-Frequency Spectrum of the Bridge under Pedestrian Loading | 169 | |
| в | Parameters and the Force Model of the PMAs | 175 | |
| С | Sensibility Analysis of Changing Modal Characteristics Based on Root Locus Plot | 179 | |
| D | Pedestrian-Induced Vibration With and Without AVC | 191 | |
| Е | List of Acronyms and Symbols | 197 | |